

Support Portal | Registry Services

Knowledgebase > Tech > EPP messages > How does the EPP-message look like which your EPP-server sends to the receiving registrar when a Registrar Transfer has been made?

How does the EPP-message look like which your EPP-server sends to the receiving registrar when a Registrar Transfer has been made?

A.A - 2024-10-31 - EPP messages

The receiving registrar is the one who initiates a change of registrar by sending in a transfer command. That command results in an answer that looks like this:

Transfer response:

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<epp xmlns="urn:ietf:params:xml:ns:epp-1.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd">
  <response>
    <result code="1000">
      <msg>Command completed successfully</msg>
    </result>
    <resData>
      <dom:trnData xsi:schemaLocation="urn:ietf:params:xml:ns:domain-1.0
domain-1.0.xsd" xmlns:dom="urn:ietf:params:xml:ns:domain-1.0">
        <dom:name>example.se</dom:name>
        <dom:trStatus>serverApproved</dom:trStatus>
        <dom:relD>RegistrarA</dom:relD>
        <dom:reDate>2009-03-15T13:45:07Z</dom:reDate>
        <dom:acID>RegistrarB</dom:acID>
        <dom:acDate>2009-03-15T00:00:00Z</dom:acDate>
      </dom:trnData>
    </resData>
  <trID>

  <cItrID>ABC-12345</cItrID><svTRID>5736a883-6ffb-425e-8b60-96008fb12812</svTRID
></trID>
</response>
```

In addition to this, a poll message is also created stating that a new contact has been created. That message looks like this:

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
```

```
<epp xmlns="urn:ietf:params:xml:ns:epp-1.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:ietf:params:xml:ns:epp-1.0 epp-1.0.xsd">
  <response>
    <result code="1301">
      <msg>Command completed successfully; ack to dequeue</msg>
    </result>
    <msgQ id="8" count="2">
      <qDate>2022-03-15T13:45:07Z</qDate>
      <msg lang="en">created contact for example.se</msg>
    </msgQ>
    <resData xmlns="urn:ietf:params:xml:ns:epp-1.0">
      <iis:createNotify xmlns:iis="urn:se:iis:xml:epp:iis-1.2"
xsi:schemaLocation="urn:se:iis:xml:epp:iis-1.2 iis-1.2.xsd">
        <con:infData xmlns:con="urn:ietf:params:xml:ns:contact-1.0"
xsi:schemaLocation="urn:ietf:params:xml:ns:contact-1.0 contact-1.0.xsd">
          <con:id>vJRftcq5T90NRe4d</con:id>
          <con:roid>CONTACT_0000052016-SE</con:roid>
          <con:status s="ok"/>
          <con:postallInfo type="loc">
            <con:name>John Doe</con:name>
            <con:org>Corporate name</con:org><con:addr>
              <con:street>Street 1</con:street>
              <con:city>City</con:city>
              <con:pc>11111</con:pc>
              <con:cc>SE</con:cc>
            </con:addr>
          </con:postallInfo>
          <con:voice x="">+46.111111</con:voice>
          <con:email>example@example.se</con:email>
          <con:clID>RegistrarA</con:clID>
          <con:crID>RegistrarA</con:crID>
          <con:crDate>2010-03-15T00:00:00Z</con:crDate>
          <con:disclose flag="0">
            </con:disclose>
          </con:infData>
        </iis:createNotify>
      </resData>
      <extension xmlns="urn:ietf:params:xml:ns:epp-1.0">
        <iis:infData xsi:schemaLocation="urn:se:iis:xml:epp:iis-1.2 iis-1.2.xsd"
xmlns:iis="urn:se:iis:xml:epp:iis-1.2">
          <iis:orgno>[SE]111111-1111</iis:orgno>
        </iis:infData>
      </extension>
    </resData>
  </response>
</epp>
```

```
</extension>
<trID>
  <clTRID>ABC-12345</clTRID>
  <svTRID>8db58683-432f-49ce-956a-f65880e42c66</svTRID>
</trID>
</response>
</epp>
```